

2016		wheel	fork	Reach		FC		Standover		Stack		Effective TT		Actual TT		Seat tube		Chain stays		BB rise		headtube	ST angle	wheelbase	
		size	travel	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	angle	effective	mm	in
Analog	S	700c	A-C 410mm	418	16,5	608,0	23,9	789,0	31,1	546	21,5	580	22,8	560,0	22,0	467	18,5	398	15,7	-49	-1,9	72,0	72,5	1001	39,4
	M		A-C 410mm	428	16,9	619,0	24,4	811,0	31,9	562	22,1	595	23,4	578,0	22,8	497	19,5	398	15,7	-49	-1,9	72,5	72,5	1012	39,8
	L		A-C 410mm	438	17,2	625,0	24,6	833,0	32,8	580	22,8	610	24,0	595,0	23,4	527	21,0	398	15,7	-49	-1,9	73,5	72,5	1018	40,1
Metropolis 1 / 2 / 3		26"	100	397	15,6	654	25,7	749,0	29,5	555	21,9	605	23,8	574,0	22,6	306	12,0	381	15,0	-4	-0,2	69,0	70,0	1036	40,8
Zircus		26"	100	397	15,6	653	25,7	738,0	29,1	574	22,6	585	23,0	571,0	22,5	335	13,0	385	15,2	-25	-1,0	69,0	72,0	1037	40,8
Movement 1 / 2		26"	100	397	15,6	653	25,7	738,0	29,1	574	22,6	585	23,0	571,0	22,5	335	13,0	385	15,2	-25	-1,0	69,0	72,0	1037	40,8
Clash JR		24"	100	361	14,2	616	24,3	703,0	27,7	527	20,7	532	20,9	520,0	20,5	305	12,0	375	14,8	-4	-0,1	68,0	72,0	994	39,1
Clash	M	26"	120	413	16,3	673	26,5	758,0	29,8	583	23,0	591	23,3	574,0	22,6	406	16,0	415	16,3	-27	-1,1	67,5	73,0	1086	42,8
	L		120	432	17,0	693	27,3	774,0	30,5	583	23,0	610	24,0	589,0	23,2	445	17,5	415	16,3	-27	-1,1	67,5	73,0	1106	43,5
Soda Slope		26"	120	418	16,5	636	25,0	782,0	30,8	560	22,0	551	21,7	540,5	21,3	348,0	13,7	390,0	15,4	7	0,3	69,0	78,0	1070	42,1
Soda Evo Air	M	27,5"	180	433	17,0	770	30,3	836,0	32,9	601	23,7	592	23,3	571,0	22,5	409	16,1	438/422	17,2/16,6	-6	-0,2	64,0	75,0	1208/1192	47,6/46,9
	L		180	454	17,9	790	31,1	830,0	32,7	601	23,7	610	24,0	587,0	23,1	445	17,5	438/422	17,2/16,6	-6	-0,2	64,0	75,0	1228/1212	48,3/47,7
Soda Evo Coil	M	27,5"	200	433	17,0	770	30,3	836,0	32,9	601	23,7	592	23,3	571,0	22,5	409	16,1	438/422	17,2/16,6	-6	-0,2	64,0	75,0	1208/1192	47,6/46,9
	L		200	454	17,9	790	31,1	830,0	32,7	601	23,7	610	24,0	587,0	23,1	445	17,5	438/422	17,2/16,6	-6	-0,2	64,0	75,0	1228/1212	48,3/47,7
Eccentric Alu 1 / Alu 2 / Cromo	S	27,5"	140	405	15,9	702	27,6	735,0	28,9	605	23,8	590	23,2	584,0	23,0	407	16,0	420	16,5	-39	-1,5	66,5	73,0	1119	44,1
	M		140	425	16,7	726	28,6	765,0	30,1	614	24,2	613	24,1	598,0	23,5	445	17,5	420	16,5	-39	-1,5	66,5	73,0	1143	45,0
	L		140	450	17,7	755	29,7	795,0	31,3	623	24,5	640	25,2	619,0	24,4	495	19,5	420	16,5	-39	-1,5	66,5	73,0	1172	46,1
Eccentric Djambo	S	27,5+	120	405	15,9	697	27,4	768,0	30,2	607	23,9	590	23,2	585,0	23,0	407	16,0	420	16,5	-39	-1,5	67,0	73,0	1114	43,9
	M		120	425	16,7	721	28,4	789,0	31,1	617	24,3	613	24,1	599,0	23,6	445	17,5	420	16,5	-39	-1,5	67,0	73,0	1138	44,8
	L		120	450	17,7	750	29,5	820,0	32,3	626	24,6	641	25,2	620,0	24,4	495	19,5	420	16,5	-39	-1,5	67,0	73,0	1167	45,9
Snabb E Carbon	M	27,5"	160	445	17,5	755	29,7	798,0	31,4	600	23,6	603	23,7	570,0	22,4	437	17,2	435	17,1	-11,5	-0,5	66,0	75,5	1185	46,7
	L		160	470	18,5	785	30,9	820,0	32,3	609	24,0	631	24,8	592,0	23,3	488	19,2	435	17,1	-11,5	-0,5	66,0	75,5	1214	47,8
Snabb E1 / E2	S	27,5"	160	420	16,5	726	28,6	801,0	31,5	591	23,3	579	22,8	545,0	21,5	399	15,7	430	16,9	-11,5	-0,5	66,0	75,5	1156	45,5
	M		160	445	17,5	755	29,7	798,0	31,4	600	23,6	603	23,7	570,0	22,4	437	17,2	430	16,9	-11,5	-0,5	66,0	75,5	1185	46,7
	L		160	470	18,5	785	30,9	820,0	32,3	609	24,0	631	24,8	592,0	23,3	488	19,2	430	16,9	-11,5	-0,5	66,0	75,5	1214	47,8
Snabb T1 / T2	S	27,5"	150	420	16,5	702	27,6	775,0	30,5	593	23,3	580	22,8	543,0	21,4	394	15,5	422	16,6	-12	-0,5	67,5	75,0	1124	44,3
	M		150	445	17,5	730	28,7	775,0	30,5	599	23,6	609	24,0	571,0	22,5	432	17,0	422	16,6	-12	-0,5	67,5	75,0	1152	45,4
	L		150	470	18,5	759	29,9	795,0	31,3	608	23,9	638	25,1	594,0	23,4	483	19,0	422	16,6	-12	-0,5	67,5	75,0	1181	46,5
Fuzz 1 / 2	S	27,5"	200	405	15,9	750	29,5	788,0	31,0	605	23,8	590	23,2	527,0	20,7	400	16,0	447/432	17,6/17	-2	-0,1	63,5	73,0	1206/1191	47,5/46,9
	M		200	440	17,3	795	31,3	792,0	31,2	605	23,8	625	24,6	557,0	21,9	400	16,0	447/432	17,6/17	-2	-0,1	63,5	73,0	1230/1216	48,4/47,9
	L		200	470	18,5	824	32,4	797,0	31,4	605	23,8	655	25,8	578,0	22,8	410	16,1	447/432	17,6/17	-2	-0,1	63,5	73,0	1260/1246	49,6/49



